



50hz 60hz Open Type Diesel Generator Single Cylinder Diesel Engine Generator

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Rated Frequency: 50hz 60hz
- Rated Output(kw): 1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3 6.8
- Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4
- Rated Voltage (V): 220V Or As Request
- Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9
- Rated Rotation Speed (r/min): 3000 3600
- Phase No.: Single Phase
- Power Factor: 1
- Insulation Grade: F
- Pole Number: 2
- Excitation Mode: Self-excitation & Constant Voltage (AVR)
- Panel Type: General Panel

for more products please visit us on dieselenginepumps.com

Product Description

GET2500E GET3500E GET6500E GET7500E GET8500E GET9500E Open Type Diesel Generator
50hz 60hz Open Type Diesel Generator Single Cylinder Vertical Four Stroke

Open type diesel generators offer several advantages that make them a popular choice in various applications. Here are some key advantages of open type diesel generators:

Cost-Effective: Open type diesel generators are generally more cost-effective compared to enclosed or soundproof generators. They often have a lower upfront cost and maintenance expenses, making them an economical choice for many users.

Easy Accessibility: The open design of these generators provides easy access to the engine and other components, simplifying maintenance and repair tasks. Technicians can quickly diagnose issues and perform routine maintenance, resulting in reduced downtime and associated costs.

Efficient Cooling: The open design allows for better air circulation around the engine, facilitating effective cooling. This helps maintain the optimal operating temperature and improves the overall efficiency and performance of the generator.

Compact and Lightweight: Open type diesel generators are typically more compact and lightweight compared to their enclosed counterparts. This makes them easier to transport, install, and maneuver, especially in situations where mobility is required.

Flexibility in Installation: The open design offers flexibility in installation options. These generators can be installed in various configurations, such as fixed installations in a designated generator room or as mobile units mounted on trailers or skids. This versatility allows for customization based on specific application requirements.

Rated Output(kw):	1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3 6.8
Rated Voltage (V):	220V Or As Request
Rated Rotation Speed (r/min):	3000 3600
Power Factor:	1
Pole Number:	2
Panel Type:	General Panel
Connection Pole:	Without
Overall Dmension(mm):	690x480x560/ 690x480x560/ 730x495x630/ 730x495x630/ 730x495x630/ 730x495x655
Working Assorting Weight (kg):	66 83 110 115 120 125
Structure Type:	Open Type
Cylinder No. -bore X Stroke (mm):	1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75
Rated Power:	2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600
Lubrication System:	Pressure Splashed
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40
Starting Motor Capacity:	12V 0.9KW/ 12V 1.2KW
Battery Capacity:	12V 20Ah/ 12V 30Ah
Fuel Tank Capacity (L):	13.5
Rated Frequency:	50hz 60hz
Max Output (kw):	2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4
Rated Currency (A):	7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9
Phase No.:	Single Phase
Insulation Grade:	F
Excitation Mode:	Self-excitation & Constant Voltage (AVR)
Receptacle:	Two Receptacles
DC 12V Output:	Connection Pole Output
Dry Weight (kg):	53 70 100 105 110 115
Noise Level (7m):	77 DB
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
Displacement(ml):	247 296 418 456 498 531
Compression Ratio:	20:01, 19:01
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel
Lube Capacity (L):	0.75 1.1 1.65
Charging Generator Capacity:	12V 8.3A
Fuel Consumption (g/kw*h):	≤280

It's important to consider the noise level and any specific noise regulations or requirements when opting for an open type diesel generator, as they tend to produce more noise compared to enclosed or soundproof models.



参数表 Specifications

[illegible]