Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Price:
- Delivery Time:

China GET

ISO CE

- Payment Terms:
- Negotiable 15-20 workdays LC, T/T, PayPal, Western Union, Smallamount payment, Money Gram



Product Specification

 Rated Frequency: 	50hz 60hz
• Rated Output(kw):	1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3 6.8
• Max Output (kw):	2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4
 Rated Voltage (V): 	220V Or As Request
• Rated Currency (A):	7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9
Rated Rotation Speed (r/min):	3000 3600
Phase No.:	Single Phase
 Power Factor: 	1
 Insulation Grade: 	F
Pole Number:	2
Excitation Mode:	Self-excitation & Constant Voltage (AVR)
• Panel Type:	General Panel

GET9500E Open Type Diesel Generator Genset For Construction Sites

Description:

Open type diesel generators are commonly used in construction sites, remote locations, agriculture, emergency backup power, and industrial settings where noise levels and environmental factors are less critical. Their compact and portable design, along with their reliable diesel engine power, make them suitable for a wide range of applications.

Rated Output(kw):	1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3 6.8
Rated Voltage (V):	220V Or As Request
Rated Rotation	3000 3600
Speed (r/min):	
Power Factor:	1
Pole Number:	2
Panel Type:	General Panel
Connection Pole:	Without
Overall	690x480x560/ 690x480x560/ 730x495x630/ 730x495x630/
Dmension(mm):	730x495x630/ 730x495x655
Working Assorting	66 83 110 115 120 125
Weight (kg):	
Structure Type:	Open Type
Cylinder Nobore X Stroke (mm):	1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75
Rated Power:	2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000- 7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600
Lubrication System:	Pressure Splashed
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40
Starting Motor	12V 0.9KW/ 12V 1.2KW
Capacity:	
Battery Capacity:	12V 20Ah/ 12V 30Ah
Fuel Tank Capacity	13.5
(L):	
Rated Frequency:	50hz 60hz
Max Output (kw):	2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4
	7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9
Phase No.:	Single Phase
Insulation Grade:	F
Excitation Mode:	Self-excitation & Constant Voltage (AVR)
Receptacle:	Two Receptacles
DC 12V Output:	Connection Pole Output
Dry Weight (kg):	53 70 100 105 110 115
Noise Level (7m):	77 DB
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
Displacement(ml):	247 296 418 456 498 531
Compression Ratio:	20:01, 19:01
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel
Lube Capacity (L):	0.75 1.1 1.65
Charging Generator Capacity:	12V 8.3A
Fuel Consumption (g/kw*h):	≤280

Application:

Emergency Backup Power: Open type diesel generators are crucial in emergency backup power systems. They are installed in hospitals, data centers, critical infrastructure, and facilities where a loss of power can have severe consequences. These generators automatically start during power outages and provide electricity until grid power is restored.

Agriculture and Farming: In agricultural applications, open type diesel generators are used to power irrigation systems, machinery, and equipment. They are employed in remote farming locations or areas without access to electricity, ensuring efficient and uninterrupted farming operations.

Events and Outdoor Functions: Open type diesel generators are commonly used at outdoor events, concerts, festivals, and construction sites. They provide power for stage lights, sound systems, temporary lighting, and other event equipment.



	G ET Wuxi Guangertai Power Machinery Co.,Ltd					
Q	13813650506	2415819289@qq.com	e	dieselenginepumps.com		
	NO.88 Shenxir	ng East Road, Wanshi Town,	, Yixing	g City,CHINA		