



8m 6m Industrial Diesel Water Pump For Agriculture Low Noise

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Model Number: GETDP150
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Type: Diesel Clean Water Pump
- Suction/discharger Port Diameter Mm(inch): 50(2'). 80(3'). 100(4'). 150(6')
- Discharge Capacity m³/h): 30 40 110 150
- Total Head Lift: 25m 26m 22m 20m
- Self-priming Time (s/4m): 80 120 180 180
- Max Suction Head: 8m 8m 8m 6m
- Rotation Speed (r/min): 3600
- Noise Level Db(A)/7m): 85
- Overall Dimension(mm): 510x455x640. 560x455x655. 650x470x700. 770x574x785
- Dry Weight: 44kg 50kg 71kg 95kg
- Engine Model: GET173F GET178F GET186FA GET192F
- Rated Power: 2.8kw 4kw 6.3kw 8.5kw
- Fuel Consumption G/kw.h: 288 285 281 281
- Displacement (cm³): 247 300 410 400

for more products please visit us on dieselenginepumps.com

Product Description

Electric Diesel Engine Pumps Diesel Engine Water Pump

Model	JBC6/10
Type	vacuum pump
Max.Flow(T/h)	48
MAX.Lift(m)	60
Rated Speed(rpm)	3600
Water Shot Height	35m
Engine	190F
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	91/100
Dimensions(mm)	
Loading Qty(20GP/40HQ)	
Model	JBC6/15
Type	vacuum pump
Max.Flow(T/h)	54
MAX.Lift(m)	80
Rated Speed(rpm)	3600
Water Shot Height	35
Engine	192
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	94/103
Dimensions(mm)	
Loading Qty(20GP/40HQ)	

Electric diesel engine pumps, also known as electric-driven diesel pumps, are versatile pumping systems that combine the power of a diesel engine with the convenience and efficiency of an electric motor. These pumps find application in various industries and sectors. Some common applications of electric diesel engine pumps include:

Utilities and Power Generation: Electric diesel engine pumps are used in utilities and power generation facilities for water intake, cooling systems, and emergency backup applications. They assist in maintaining proper water circulation and cooling in power plants, ensuring efficient operations and preventing equipment damage.

Environmental Remediation: Electric diesel engine pumps are employed in environmental remediation projects to pump and transfer contaminated water, slurry, or other fluids during cleanup and remediation processes.



参数表 Specifications

Model & Serial	190F/100	190F/100	190F/100	190F/100
产品名称 Type	清水泵	清水泵	清水泵	清水泵
额定流量 Rated Discharge Port Diameter	48(T/h)	54(T/h)	54(T/h)	54(T/h)
最大流量 Max. Flow	48	54	54	54
额定扬程 Rated Head	35	35	35	35
最大扬程 Max. Head	60	80	80	80
额定功率 Rated Power	190	190	190	190
最大功率 Max. Power	190	190	190	190
额定转速 Rated Speed	3600	3600	3600	3600
最大转速 Max. Speed	3600	3600	3600	3600
额定重量 Rated Weight	91	94	94	94
最大重量 Max. Weight	100	103	103	103
额定尺寸 Rated Dimension	1000*500*500	1000*500*500	1000*500*500	1000*500*500
额定功率 Rated Power	190	190	190	190
最大功率 Max. Power	190	190	190	190
额定流量 Rated Discharge	48	54	54	54
最大流量 Max. Flow	48	54	54	54
额定扬程 Rated Head	35	35	35	35
最大扬程 Max. Head	60	80	80	80
额定功率 Rated Power	190	190	190	190
最大功率 Max. Power	190	190	190	190
额定转速 Rated Speed	3600	3600	3600	3600
最大转速 Max. Speed	3600	3600	3600	3600
额定重量 Rated Weight	91	94	94	94
最大重量 Max. Weight	100	103	103	103
额定尺寸 Rated Dimension	1000*500*500	1000*500*500	1000*500*500	1000*500*500



Wuxi Guangertai Power Machinery Co.,Ltd



13813650506



2415819289@qq.com



diesenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA