

Fire Driver Diesel Engine Pumps 2.8KW 4KW Diesel Clean Water **Pump**

Basic Information

. Place of Origin: China Brand Name: **GET** ISO CE · Certification: GETDP150 Model Number: • Price: Negotiable Delivery Time: 15-20 workdays

LC, T/T, PayPal, Western Union, Small-• Payment Terms: amount payment, Money Gram



Product Specification

. Type: Diesel Clean Water Pump Suction/discharger Port 50(2'). 80(3'). 100(4'). 150(6')

Diameter Mm(inch):

• Discharge Capacity m³/h): 30 40 110 150 • Total Head Lift: 25m 26m 22m 20m 80 120 180 180 Self-priming Time (s/4m): Max Suction Head: 8m 8m 8m 6m

• Rotation Speed (r/min): 3600 85 • Noise Level Db(A)/7m):

• Overall Dimension(mm): 510x455x640. 560x455x655. 650x470x700.

770x574x785

• Dry Weight: 44kg 50kg 71kg 95kg

GET173F GET178F GET186FA GET192F . Engine Model:

Rated Power: 2.8kw 4kw 6.3kw 8.5kw

• Fuel Consumption G/kw.h: 288 285 281 281 Disclessor (2003). 047 000 440 400

Product Description

Heavy Duty Diesel Fire Pump Diesel Engine Pumps

Oil and Gas: Electric diesel engine pumps are utilized in the oil and gas industry for various purposes. They are employed in well stimulation operations, water injection for enhanced oil recovery, and fluid transfer during drilling and production processes. These pumps can handle high pressures and deliver fluids over long distances.

Municipal and Industrial Water Supply: Electric diesel engine pumps are extensively used in municipal water supply systems and industrial facilities. They help in drawing water from rivers, lakes, or reservoirs and pumping it to treatment plants or distribution networks. They can also provide water for industrial processes and firefighting applications.

Emergency Response: Electric diesel engine pumps are essential components of emergency response systems. They are used during flood control efforts, emergency dewatering, or in disaster situations where quick water transfer or removal is required.

Model	JBC6/10
Туре	vacuum pump
Max.Flow(T/h)	48
MAX.Lift(m)	60
Rated Speed(rpm)	3600
Water Shot Height	35m
Engine	190F
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	91/100
Dimensions(mm)	
Loading Qty(20GP/40HQ)	
Model	JBC6/15
Туре	vacuum pump
Max.Flow(T/h)	54
MAX.Lift(m)	80
Rated Speed(rpm)	3600
Water Shot Height	35
Engine	192
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	94/103
Dimensions(mm)	
Loading Qty(20GP/40HQ)	



GET Wuxi Guangertai Power Machinery Co.,Ltd



13813650506



2415819289@qq.com



@ dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA