

13.5L High Pressure Inline Fuel Pump GET173F Electric **Start**

Basic Information

. Place of Origin: China Brand Name: **GET** ISO CE · Certification: GETDP150 Model Number: • Price: Negotiable Delivery Time: 15-20 workdays

LC, T/T, PayPal, Western Union, Small-• Payment Terms: amount payment, Money Gram



Product Specification

. Type: Diesel Clean Water Pump Suction/discharger Port 50(2'). 80(3'). 100(4'). 150(6')

Diameter Mm(inch):

• Discharge Capacity m³/h): 30 40 110 150 • Total Head Lift: 25m 26m 22m 20m 80 120 180 180 Self-priming Time (s/4m): Max Suction Head: 8m 8m 8m 6m

• Rotation Speed (r/min): 3600 85 • Noise Level Db(A)/7m):

• Overall Dimension(mm): 510x455x640. 560x455x655. 650x470x700.

770x574x785

• Dry Weight: 44kg 50kg 71kg 95kg

GET173F GET178F GET186FA GET192F . Engine Model:

Rated Power: 2.8kw 4kw 6.3kw 8.5kw

 Fuel Consumption G/kw.h: 288 285 281 281 Disclessor (2003). 047 000 440 400

Product Description

High Pressure Inline Diesel Fuel Pump Diesel Fire Pump Electric Start

Wastewater Management: Electric diesel engine pumps are employed in wastewater treatment plants for pumping sewage, sludge, or wastewater. They help in the transfer of fluids within the treatment facility, as well as in the transportation of treated effluent for discharge or reuse.

Marine and Offshore: Electric diesel engine pumps are utilized in marine and offshore applications for various purposes, including bilge pumping, ballast water management, fire protection systems, and general fluid transfer on ships, vessels, and offshore platforms.

onshore pianornis.		
Model	JBC6/10	
Туре	vacuum pump	
Max.Flow(T/h)	48	
MAX.Lift(m)	60	
Rated Speed(rpm)	3600	
Water Shot Height	35m	
Engine	190F	
Maximum Suction Height(m)	7	
Self-priming Time(S)	20	
Discharge Port Diameter(mm)	65	
N.W/G.W(KG)	91/100	
Dimensions(mm)		
Loading Qty(20GP/40HQ)		
Model	JBC6/15	_
Туре	vacuum pump	
Max.Flow(T/h)	54	
MAX.Lift(m)	80	
Rated Speed(rpm)	3600	
Water Shot Height	35	
Engine	192	
Maximum Suction Height(m)	7	
Self-priming Time(S)	20	
Discharge Port Diameter(mm)	65	
N.W/G.W(KG)	94/103	
Dimensions(mm)		
Loading Qty(20GP/40HQ)		
		_



GET Wuxi Guangertai Power Machinery Co.,Ltd



13813650506



2415819289@qq.com



dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA